

SERIE 112CD

## 112A-CD

**AVO - Wheel with conductive rubber tyre for industry, diameter 100mm ean 17108**

**Material:** Conductive Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

**Product line:** Antistatic/Conductive

**EAN13:**8018793171083

**EAN5:**17108

**Article code:**03112A01000CA



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 70 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                        |
|-----------------------------|------------------------|
| Diameter (mm)               | 100                    |
| Band width (mm)             | 30                     |
| Hub width (mm)              | 37                     |
| Hub version                 | Ball bearing           |
| Wheel hole (mm)             | 8                      |
| Bearing seat (mm)           | /                      |
| Dynamic load capacity (DaN) | 70                     |
| Colour                      | Black                  |
| Material                    | Conductive Rubber tyre |
| Box pieces                  | /                      |
| Hardness scale              | Shore A                |
| Hardness                    | 80                     |

## Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |