

SERIE 16A-CD

## 16A-CD

AVO - Wheel with conductive rubber tyre for industry, diameter 100mm ean 22164

**Material:** Conductive Rubber tyre

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel with conductive Rubber tread 68 Shore A and conductive Polyamide 6 centre. Hub with through bore, with roller cage or shielded ball bearings assembled with central spacer. The 16A-CD wheel can be assembled with all medium and heavy duty castors.

**Product line:** Antistatic/Conductive

**EAN13:**8018793221641 **EAN5:**22164 **Article code:**14C16A0100ECA



### Features

**Minimum temperature:** -20 **Maximum temperature:** 70 **Dynamic load capacity:** 180 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	32X9
Dynamic load capacity (DaN)	180
Colour	Black
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/