

SERIE 16A-CD

16A-CD

AVO - Wheel with conductive rubber tyre for industry, diameter 160mm ean 21309

Material: Conductive Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with conductive Rubber tread 68 Shore A and conductive Polyamide 6 centre. Hub with through bore, with roller cage or shielded ball bearings assembled with central spacer. The 16A-CD wheel can be assembled with all medium and heavy duty castors.

Product line: Antistatic/Conductive

EAN13:8018793213097

EAN5:21309

Article code:14C16A0160ECA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Black
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/