

SERIE 112CD

112CD

AVO - Wheel with conductive rubber tyre for industry, diameter 80mm ean 13209

Material: Conductive Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

Product line: Antistatic/Conductive

EAN13:8018793132091

EAN5:13209

Article code:03112000800RA



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 50 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Black
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/