

SERIE 112CD

## 80-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 125mm ean 21263

**Material:** Conductive Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793212632

**EAN5:**21263

**Article code:**01080001250RA



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 100 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                        |
|-----------------------------|------------------------|
| Diameter (mm)               | 125                    |
| Band width (mm)             | 38                     |
| Hub width (mm)              | 50                     |
| Hub version                 | Roller bearing         |
| Wheel hole (mm)             | 15                     |
| Bearing seat (mm)           | /                      |
| Dynamic load capacity (DaN) | 100                    |
| Colour                      | Black                  |
| Material                    | Conductive Rubber tyre |
| Box pieces                  | /                      |
| Hardness scale              | Shore A                |
| Hardness                    | 80                     |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 8,5X12     |
| Offset (mm)                | 42         |
| Ground clearance (mm)      | 155        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 130        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |