

SERIE 112CD

## 80B-CD

**AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 125mm ean 21598**

**Material:** Conductive Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793215985

**EAN5:**21598

**Article code:**01080B01250RA



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 100 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                        |
|-----------------------------|------------------------|
| Diameter (mm)               | 125                    |
| Band width (mm)             | 38                     |
| Hub width (mm)              | 50                     |
| Hub version                 | Roller bearing         |
| Wheel hole (mm)             | 15                     |
| Bearing seat (mm)           | /                      |
| Dynamic load capacity (DaN) | 100                    |
| Colour                      | Black                  |
| Material                    | Conductive Rubber tyre |
| Box pieces                  | /                      |
| Hardness scale              | Shore A                |
| Hardness                    | 80                     |

## Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 42                                        |
| Ground clearance (mm)      | 150                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 130                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle                                      |
| Brake                      | /                                         |
| Plain axle                 | 22X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |