

SERIE 112CD

80-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 150mm ean 21265

Material: Conductive Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13:8018793212656

EAN5:21265

Article code:01080001500RA



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 135 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Black
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11X16
Offset (mm)	45
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized