

SERIE 112CD

80A-CD

AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 180mm

Material: Conductive Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13:/ EAN5:/ Article code:01080A01800RA



Features

Minimum temperature: -25

Maximum temperature: 85

Dynamic load capacity: 170 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Conductive Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	225
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized