

SERIE 112CD

## 103-CD

**AVO - Wheel with conductive rubber tyre and steel castor for industry, diameter 200mm**

**Material:** Conductive Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:/ EAN5:/ Article code:**03103002000RA



## Features

**Minimum temperature:** -25

**Maximum temperature:** 85

**Dynamic load capacity:** 205 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                        |
|-----------------------------|------------------------|
| Diameter (mm)               | 200                    |
| Band width (mm)             | 50                     |
| Hub width (mm)              | 58                     |
| Hub version                 | Roller bearing         |
| Wheel hole (mm)             | 20                     |
| Bearing seat (mm)           | /                      |
| Dynamic load capacity (DaN) | 205                    |
| Colour                      | Black                  |
| Material                    | Conductive Rubber tyre |
| Box pieces                  | /                      |
| Hardness scale              | Shore A                |
| Hardness                    | 80                     |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 140X110          |
| Plate hole spacing (mm)    | 105X080          |
| Plate hole size (mm)       | 11X16            |
| Offset (mm)                | 55               |
| Ground clearance (mm)      | 235              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 260              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Front            |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |