

SERIE 16

40

AVO - Wheel with elastic rubber tyre and steel castor for industry,  
diameter 150mm ean 06754

**Material:** Elastic Rubber  
tyre

**Core:** Cast  
Iron

**Application field:**  
Industry

**Description:**

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.  
Hub on shielded ball bearings assembled with central space.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double  
rim of balls fitted in hardening steel thrust-bearings, with plate. Assembled with  
self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793067546

**EAN5:**06754

**Article code:**1404000150ECG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 400 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 150                 |
| Band width (mm)             | 45                  |
| Hub width (mm)              | 45                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 20                  |
| Bearing seat (mm)           | 47X14               |
| Dynamic load capacity (DaN) | 400                 |
| Colour                      | Black               |
| Material                    | Elastic Rubber tyre |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 68                  |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 135X110    |
| Plate hole spacing (mm)    | 105X080    |
| Plate hole size (mm)       | 13X16      |
| Offset (mm)                | 50         |
| Ground clearance (mm)      | 189        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 500        |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |