

SERIE 16

40BISB

AVO - Wheel with cushion rubber tyre and steel castor for industry,
diameter 150mm ean 20476

Material: Cushion Rubber tyre **Core:** Cast Iron **Scope:** Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.
Hub on shielded ball bearings assembled with central space.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double
rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake.
Assembled with self-locking nut.

Product line: Rubber tyre

EAN13: 8018793204767 **EAN5:** 20476 **Article code:** 14040BF150ECG



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 400 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 69

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	45
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	400
Colour	Black
Material	Cushion Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	69

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	50
Ground clearance (mm)	184
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized