

SERIE 16

40BISB

AVO - Wheel with cushion rubber tyre and steel castor for industry,
diameter 200mm ean 20477

Material: Cushion Rubber tyre **Core:** Cast Iron **Scope:** Industry

Description:

Wheel with black elastic rubber tyre 68 Shore A and mechanical cast iron centre.
Hub on shielded ball bearings assembled with central space.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double
rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake.
Assembled with self-locking nut.

Product line: Rubber tyre

EAN13: 8018793204774 **EAN5:** 20477 **Article code:** 14040BF200ECG



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 600 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 69

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 200 |
| Band width (mm) | 60 |
| Hub width (mm) | 60 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 600 |
| Colour | Black |
| Material | Cushion Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 69 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 57 |
| Ground clearance (mm) | 244 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 750 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 25X65 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |