

SERIE 18

34A

AVO - Wheel with cushion rubber tyre and steel castor for industry, diameter 250mm ean 06721

Material: Cushion Rubber tyre

Core: Cast Iron

Application field: Industry

Description:

CUSHION rubber wheel tyre 69 Shore A and mechanical cast iron centre. Hub on shielded ball bearings assembled with central space.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793067218

EAN5:06721

Article code:13034A0250CC



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 1500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 69

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	80
Hub width (mm)	45
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	1500
Colour	Black
Material	Cushion Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	69

Support data

Plate size (mm)	175X140
Plate hole spacing (mm)	140X105
Plate hole size (mm)	15
Offset (mm)	/
Ground clearance (mm)	305
Castor hole (mm)	/
Static load capacity (DaN)	1880
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted