

SERIE 18

34BIS

AVO - Wheel with cushion rubber tyre and steel castor for industry, diameter 250mm ean 19187

Material: Cushion Rubber tyre

Core: Cast Iron

Application field: Industry

Description:

CUSHION rubber wheel tyre 69 Shore A and mechanical cast iron centre. Hub on shielded ball bearings assembled with central space.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate and rear brake. Black epoxy paint.

Product line: Rubber tyre

EAN13:8018793191876 **EAN5:**19187 **Article code:**130340F250OCC



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 1500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 69

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 250 |
| Band width (mm) | 80 |
| Hub width (mm) | 45 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 25 |
| Bearing seat (mm) | 52X15 |
| Dynamic load capacity (DaN) | 1500 |
| Colour | Black |
| Material | Cushion Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 69 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 175X140 |
| Plate hole spacing (mm) | 140X105 |
| Plate hole size (mm) | 15 |
| Offset (mm) | 80 |
| Ground clearance (mm) | 305 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 1880 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |