

SERIE 16A

16A

**AVO - Wheel with elastic rubber tyre for industry, diameter 150mm
ean 17475**

Material: Elastic Rubber
tyre

Core:
Aluminum

Application field:
Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Rubber tyre

EAN13:8018793174756

EAN5:17475

Article code:8316AN2015050



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	32X9
Dynamic load capacity (DaN)	300
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/