

SERIE 16N-N

16N-N

AVO - Wheel with elastic rubber tyre for industry, diameter 160mm
ean 16426

Material: Elastic Rubber
tyre

Core: Polyamide
6

Application field:
Industry

Description:

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Rubber tyre

EAN13:8018793164269

EAN5:16426

Article code:8317N16N1615C



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 350 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	350
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/