

SERIE 602

602

**AVO - Wheel with elastic rubber tyre for industry, diameter 300mm
ean 15048**

Material: Elastic Rubber
tyre

Core: Electro-welded
steel

Application field:
Industry

Description:

Wheel with solid elastic rubber tyre 76 Shore A and electrowelded steel centre.
Hub on shielded 2RS waterproof ball bearings or SKF ball bearings.

Product line: Rubber tyre

EAN13:8018793150484

EAN5:15048

Article code:14602RS300100



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 1500 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 76

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	100
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	35
Bearing seat (mm)	FORO 72
Dynamic load capacity (DaN)	1500
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	76

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/