

SERIE 16A

16A

AVO - Wheel with elastic rubber tyre for industry, diameter 300mm
ean 24515

Material: / **Core:** Aluminum **Scope:** Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Rubber tyre

EAN13:8018793245159 **EAN5:**24515 **Article code:**8316AN2530060



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 800 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	300
Band width (mm)	60
Hub width (mm)	70
Hub version	Ball bearing
Wheel hole (mm)	215
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	800
Colour	Black
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Stem	/
Stem type	/
Finishing	/