

SERIE 16NX

366XA

AVO - Wheel with elastic rubber tyre and aisi 316 stainless steel castor for industry, diameter 100mm ean 22203

Material: Elastic Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre. Hub on stainless steel roller bearings.

Medium duty castors:

Made of pressed stainless steel AISI 316, fixed.

Product line: Stainless steel

EAN13:8018793222037

EAN5:22203

Article code:0X366A0101NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel