

SERIE 16NX

366X

AVO - Wheel with elastic rubber tyre and aisi 316 stainless steel castor for industry, diameter 80mm ean 24781

Material: Elastic Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre. Hub on stainless steel roller bearings.

Medium duty castors:


Made of pressed stainless steel AISI 316, turning on double rim of stainless-steel balls AISI 316, with plate. Dust cover ring on the balls.

Product line: Stainless steel

EAN13: 8018793247818

EAN5: 24781

Article code: 0X36600081NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 120 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	107
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel