

SERIE 16A

39B

AVO - Wheel made of elastic rubber tyre with steel castor for industry, diameter 100mm ean 14152

Material: Elastic Rubber tyre **Core:** Aluminum **Scope:** Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793141529 **EAN5:**14152 **Article code:**14039B0100ECA



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 160 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

| | |
|-----------------------------|---------------------|
| Diameter (mm) | 100 |
| Band width (mm) | 40 |
| Hub width (mm) | 40 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 32X9 |
| Dynamic load capacity (DaN) | 160 |
| Colour | Black |
| Material | Elastic Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 68 |

Support data

| | |
|----------------------------|--------------------------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 36 |
| Ground clearance (mm) | 131 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 200 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Stem | 22X50 |
| Stem type | Stem(on request threaded stem) |
| Finishing | Galvanized |