Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 16A-BU

39BISB-BU

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 14201

Material: Elastic Rubber tyre

Core: Aluminum Application field:

Industry

Description:

Wheel with blue elastic cut-resistant rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793142014

EAN5:14201

Article code:14039BF100BCA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 160 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- ConcreteGrid
- Stoneware

Wheel data

| Diameter (mm) | 100 |
|-----------------------------|---------------------|
| Band width (mm) | 40 |
| Hub width (mm) | 40 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 32X9 |
| Dynamic load capacity (DaN) | 160 |
| Colour | Blue |
| Material | Elastic Rubber tyre |
| Box pieces | 1 |
| Hardness scale | Shore A |
| Hardness | 68 |

Support data

| Plate size (mm) | 1 |
|----------------------------|---|
| Plate hole spacing (mm) | 1 |
| Plate hole size (mm) | 1 |
| Offset (mm) | 36 |
| Ground clearance (mm) | 131 |
| Castor hole (mm) | 1 |
| Static load capacity (DaN) | 200 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |