

SERIE 16A-BU

## 39BISB-BU

AVO - Wheel with elastic rubber tyre and steel castor for industry,  
diameter 100mm ean 14201

**Material:** Elastic Rubber tyre    **Core:** Aluminum    **Scope:** Industry

**Description:**

Wheel with blue elastic cut-resistant rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793142014    **EAN5:**14201    **Article code:**14039BF100BCA



## Features

**Minimum temperature:** -20    **Maximum temperature:** 70    **Dynamic load capacity:** 160 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	32X9
Dynamic load capacity (DaN)	160
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	/
Static load capacity (DaN)	200
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle
Finishing	Galvanized