Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 16N

67BISB

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 17708

Material: Elastic RubberCore: PolyamideApplication field:tyre6Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793177085 **EAN5**:17708 **Article code**:00067BF101NRB



Features

Minimum temperature: -20 Maximum temperature: 70 Dynamic load capacity: 200 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	200
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	36
Ground clearance (mm)	131
Castor hole (mm)	1
Static load capacity (DaN)	250
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized