

SERIE 16N-T

66A-T

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 17747

Material: Elastic Rubber tyre

Core: Glass-filled polyamide 6

Application field: Industry

Description:

Wheel with elastic high temperature rubber tyre 68 Shore A and fiberglass Polyamide centre. Hub on plain bore. Teflon inox bush available on request.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793177474

EAN5:17747

Article code:00066A010TNFN



Features

Minimum temperature: -20

Maximum temperature: 250

Dynamic load capacity: 80 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	80
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized