

SERIE 16N-N

## 66ANTF-N

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 18938

**Material:** Elastic Rubber tyre

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

In acciaio stampato zinco-cromato rotante su doppia corona di sfere, con foro e freno anteriore. Assemblaggio con dado autobloccante.

**Product line:** Rubber tyre

**EAN13:** 8018793189385

**EAN5:** 18938

**Article code:** 00066FA101NRN



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 120 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 100                 |
| Band width (mm)             | 36                  |
| Hub width (mm)              | 40                  |
| Hub version                 | Roller bearing      |
| Wheel hole (mm)             | 12                  |
| Bearing seat (mm)           | /                   |
| Dynamic load capacity (DaN) | 120                 |
| Colour                      | Black               |
| Material                    | Elastic Rubber tyre |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 68                  |

## Support data

|                            |                      |
|----------------------------|----------------------|
| Plate size (mm)            | /                    |
| Plate hole spacing (mm)    | /                    |
| Plate hole size (mm)       | /                    |
| Offset (mm)                | 37                   |
| Ground clearance (mm)      | 126                  |
| Castor hole (mm)           | 12                   |
| Static load capacity (DaN) | 150                  |
| Structure                  | Swivel               |
| Version                    | Bolt hole with brake |
| Brake                      | Front                |
| Plain axle                 | /                    |
| Stem type                  | /                    |
| Finishing                  | Galvanized           |