

SERIE 16N-N

## 66ANTB-N

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 20524

**Material:** Elastic Rubber tyre

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793205245

**EAN5:**20524

**Article code:**00066BA100NRN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 120 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized