

SERIE 16N-T

## 66ANTB-T

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 100mm ean 27932

**Material:** Elastic Rubber tyre

**Core:** Glass-filled polyamide 6

**Application field:** Industry

**Description:**

Wheel with elastic high temperature rubber tyre 68 Shore A and fiberglass Polyamide centre. Hub on plain bore. Teflon inox bush available on request.

**Medium duty castors:**

In zinc-chromium plated pressed steel turning on double rim of balls. Assembled with self locking nut.

**Product line:** High temperature

EAN13:8018793279321 EAN5:27932 Article code:00066BA10TNFN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 250

**Dynamic load capacity:** 80 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	80
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized