

SERIE 16A

39BISB

AVO - Wheel made of elastic rubber tyre with steel castor for industry, diameter 125mm ean 10800

Material: Elastic Rubber tyre **Core:** Aluminum **Scope:** Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793108003 **EAN5:**10800 **Article code:**14039BF125ECA



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 225 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	225
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	161
Castor hole (mm)	/
Static load capacity (DaN)	275
Structure	Swivel
Version	Axle with brake
Brake	Rear
Stem	22X50
Stem type	Stem(on request threaded stem)
Finishing	Galvanized