

SERIE 16A-BU

36-BU

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 125mm ean 20468

Material: Elastic Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with blue elastic cut-resistant rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793204682

EAN5:20468

Article code:1403600124BCA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	170
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	42
Ground clearance (mm)	153
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized