

SERIE 16N

67A

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 125mm ean 20788

Material: Elastic Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793207881

EAN5:20788

Article code:00067A0126NCB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 250 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	36
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	250
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	/
Ground clearance (mm)	166
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized