

SERIE 16N-N

## 67B-N

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 125mm ean 20823

**Material:** Elastic Rubber tyre

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793208239

**EAN5:**20823

**Article code:**00067B0126NRN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 250 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	125
Band width (mm)	36
Hub width (mm)	48
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	250
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized