

SERIE 16A

36A

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 150mm ean 23496

Material: Elastic Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793234962

EAN5:23496

Article code:14036A0150ECA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	185
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized