

SERIE 16A-BU

## 39BIS-BU

**AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 160mm ean 10819**

**Material:** Elastic Rubber tyre

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel with blue elastic cut-resistant rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793108195

**EAN5:**10819

**Article code:**14039F0160BCA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 160                 |
| Band width (mm)             | 50                  |
| Hub width (mm)              | 60                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 20                  |
| Bearing seat (mm)           | 47X14               |
| Dynamic load capacity (DaN) | 300                 |
| Colour                      | Blue                |
| Material                    | Elastic Rubber tyre |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 68                  |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 135X110          |
| Plate hole spacing (mm)    | 105X080          |
| Plate hole size (mm)       | 13X16            |
| Offset (mm)                | 57               |
| Ground clearance (mm)      | 216              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 380              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Rear             |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |