

SERIE 16N-AM

## 67BISB-AM

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 160mm ean 14397

**Material:** Elastic Rubber tyre

**Core:** Polyamide 6

**Application field:** Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793143974

**EAN5:**14397

**Article code:**00067BF160NRG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized