

SERIE 16N-AM

67BIS-AM

AVO - Wheel with elastic rubber tyre and steel castor for industry,
diameter 160mm ean 14417

Material: Elastic Rubber
tyre

Core: Polyamide
6

Application field:
Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

Heavy-Duty Castors:

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with plate and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793144179

EAN5:14417

Article code:000670F160NCG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	135X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	13X16
Offset (mm)	57
Ground clearance (mm)	216
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized