

SERIE 16N

## 67BISB

AVO - Wheel with elastic rubber tyre and steel castor for industry,  
diameter 160mm ean 14419

**Material:** Elastic Rubber tyre    **Core:** Polyamide 6    **Scope:** Industry

**Description:**

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793144193    **EAN5:**14419    **Article code:**00067BF160NCB



## Features

**Minimum temperature:** -20    **Maximum temperature:** 70    **Dynamic load capacity:** 300 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	57
Ground clearance (mm)	209
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X65
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized