

SERIE 16N-N

66F-N

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 160mm ean 20804

Material: Elastic Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13: 8018793208048

EAN5: 20804

Article code: 00066F0160NRN



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized