

SERIE 16A

## 39BISB

**AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 200mm ean 10808**

**Material:** Elastic Rubber tyre

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Heavy-Duty Castors:**

Made of zinc-chromium plated pressed steel, high thickness, turning on double rim of balls fitted in hardening steel thrust-bearings, with stem and rear brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793108089

**EAN5:**10808

**Article code:**14039BF200ECA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 400 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                     |
|-----------------------------|---------------------|
| Diameter (mm)               | 200                 |
| Band width (mm)             | 50                  |
| Hub width (mm)              | 60                  |
| Hub version                 | Ball bearing        |
| Wheel hole (mm)             | 20                  |
| Bearing seat (mm)           | 47X14               |
| Dynamic load capacity (DaN) | 400                 |
| Colour                      | Black               |
| Material                    | Elastic Rubber tyre |
| Box pieces                  | /                   |
| Hardness scale              | Shore A             |
| Hardness                    | 68                  |

## Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 57                                        |
| Ground clearance (mm)      | 251                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 500                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Rear                                      |
| Plain axle                 | 25X65                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |