

SERIE 16N-N

66ANT-N

AVO - Wheel with elastic rubber tyre with steelcastor for industry,
diameter 200mm ean 23718

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Wheel with black elastic cut-resistant rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Product line: Rubber tyre

EAN13:8018793237185 **EAN5:**23718 **Article code:**000660F200NRN



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 300 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Black
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized