

SERIE 16A

36A

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 250mm ean 14147

Material: Elastic Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with black elastic rubber coating, 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793141475

EAN5:14147

Article code:14036A0250ECA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 400 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	52X15
Dynamic load capacity (DaN)	400
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	/
Ground clearance (mm)	302
Castor hole (mm)	/
Static load capacity (DaN)	500
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized