

SERIE 16N-T

66B-T

AVO - Wheel with elastic rubber tyre and steel castor for industry, diameter 80mm ean 27672

Material: Elastic
Rubber tyre

Core: Glass-filled
polyamide 6

Application field:
Industry

Description:

Wheel with elastic high temperature rubber tyre 68 Shore A and fiberglass Polyamide centre. Hub on plain bore. Teflon inox bush available on request.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793276726 **EAN5:**27672 **Article code:**00066B080TNFN



Features

Minimum temperature: -20

Maximum temperature: 250

Dynamic load capacity: 80 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	80
Colour	Black
Material	Elastic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Axle
Brake	/
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized