

SERIE 604

604

AVO - Wheel with solid rubber tyre for industry, diameter 306mm
ean 24025

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Product line: Rubber tyre, Pneumatic

EAN13:8018793240253 **EAN5:**24025 **Article code:**1460400306094



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 550 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	306
Band width (mm)	93
Hub width (mm)	65
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	47X12
Dynamic load capacity (DaN)	550
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/