Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



SERIE 112

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 100mm ean 05131

Material: Solid Rubber tyre Core: Steel Application field: Industry

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793051316 EAN5:05131 Article code:03103B01000RN



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 70 DaN

Rotation: Roller bearing Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	70
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	1
Static load capacity (DaN)	90
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized