

SERIE 112B

90ANTB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 100mm ean 11109

Material: Solid Rubber tyre

Core: Polypropylene

Application field: Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793111096

EAN5:11109

Article code:02090BA1000RN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized