

SERIE 112

# 103

**AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 125mm ean 05147**

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793051477    **EAN5:**05147    **Article code:**03103S01250BN



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 100 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                   |
|-----------------------------|-------------------|
| Diameter (mm)               | 125               |
| Band width (mm)             | 38                |
| Hub width (mm)              | 50                |
| Hub version                 | Plain bore        |
| Wheel hole (mm)             | 15                |
| Bearing seat (mm)           | /                 |
| Dynamic load capacity (DaN) | 100               |
| Colour                      | Black             |
| Material                    | Solid Rubber tyre |
| Box pieces                  | /                 |
| Hardness scale              | Shore A           |
| Hardness                    | 80                |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 100X085          |
| Plate hole spacing (mm)    | 080X060          |
| Plate hole size (mm)       | 8,5X12           |
| Offset (mm)                | 42               |
| Ground clearance (mm)      | 155              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 130              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Front            |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |