

SERIE 112

80A

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 125mm ean 10996

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793109963 **EAN5:**10996 **Article code:**01080SA1250CN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 100 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	43
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized