Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 112

103B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 125mm ean 13076

Material: Solid Rubber tyre Core: Steel Application field: Industry

Description

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

**EAN13**:8018793130769 **EAN5**:13076 **Article code**:03103SB1250RN



## **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 100 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

## **Flooring**

- Asphalt
- ConcreteStoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	100
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	1
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized