

SERIE 112B

90

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 125mm ean 19890

**Material:** Solid Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793198905 **EAN5:**19890 **Article code:**02090001251RN



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 100 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

## Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	42
Ground clearance (mm)	42
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized