

SERIE 112

80BIS

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 140mm ean 04224

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793042246 **EAN5:**04224 **Article code:**01080F01400RN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 115 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------|
| Diameter (mm) | 140 |
| Band width (mm) | 38 |
| Hub width (mm) | 50 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 115 |
| Colour | Black |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|------------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 45 |
| Ground clearance (mm) | 176 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 150 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Rear |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |